

# **GW4 G BUILD ENGINE**

GW4 15, GW4 18

Power range: 40—48 kW; 53.6—64.3 bhp Fixed speed; full-load speed ranges: 1500 and 1800 r/min

# NATURALLY ASPIRATED HEAVY DUTY G BUILD DIESEL ENGINE

# **SPECIAL ATTRIBUTES**


- · suitable for generating sets
- 250-hour service intervals
- continuous operation in ambient temperatures up to 45°C (113°F)
- cold start down to –20°C (-4°F)

## **BASIC ENGINE CHARACTERISTICS**

- four cylinders
- · diesel fuelled
- direct injection
- · liquid cooled
- naturally aspirated

# **DESIGN FEATURES AND EQUIPMENT**

- standard oil and fuel filters
- 12V electric start (optional 24V)
- anti clockwise rotation, looking on flywheel end
- SAE 10" and 11.5" flywheel
- SAE3 flywheel housing
- radiator with fan guard
- cast-iron crankcase
- self-vent fuel system
- inline fuel injection pump
- flywheel with ring gear
- air cleaner
- oil pressure sender/switch combination
- water temperature sender/switch combination
- spin-on lubricating-oil filter
- fuel filter / agglomerator
- · inlet and exhaust manifolds
- operators' handbook




**GW4 G BUILD ENGINE** 

POWER OUTPUTS TO ISO 3046							
	r/min	1500	1800				
Continuous	kW	40.0	44.0				
Power	bhp	53.6	59.0				
Overload	kW	44.0	48.4				
Power	bhp	59.0	64.9				

FUEL CONSUMPTION					
r/min	1500	1800			
litre/hr @ 100% power (continuous power)	10.8	11.9			

**Notes:** 1. Power ratings are measured at the flywheel end. 2. Power ratings and fuel consumption figures apply to a fully run-in, non-derated engine without a radiator and fan fitted, and without power-absorbing accessories or transmission equipment.

APPROXIMATE DIMENSIONS AND WEIGHT					
Length (A)	mm	1260			
	in	49.6			
Height (B)	mm	950			
	in	37.4			
Width (C)	mm	706			
Width (C)	in	27.8			
Dry Weight	kg	540			
	lb	1190			



# **RATING DEFINITIONS, TO ISO 3046**

ISO Standard Conditions
Barometric pressure 100 kPa
Relative humidity 30%
Ambient temperature at air inlet manifold 25°C

#### Fixed speed power: continuous power (ICN)

The power in kW which the engine is capable of delivering continuously at the stated crankshaft speed, under ISO standard conditions, measured at the flywheel without power-absorbing accessories, provided that the engine is overhauled and maintained in good operating condition and that fuel to BS EN 590 Class A1 or A2, and lubricating oils to the correct performance specification and viscosity classification as recommended by Lister Petter Limited, are used.

# Fixed speed power: overload power (ICXN)

The maximum power in kW which the engine is capable of delivering intermittently at the stated crankshaft speed for a period not exceeding one hour in any period of twelve hours' continuous running, immediately after working at the continuous power, under

TECHNICAL DATA						
Model		GW4 15	GW4 18			
Number of cylinde	4					
Firing order (number 1 cylinder is at g	1342					
Type of fuel injection	Direct					
Aspiration	Natural					
Direction of rotation, looking on flywheel		Anti clockwise				
	mm	100				
Cylinder bore	in	3.94				
Chroke	mm	127				
Stroke	in	5				
Total or Parker and St.	litre	3.99				
Total cylinder capacity	in <sup>3</sup>	243.3				
Compression ratio		16.5:1				
Rated maximum full-load (r/min)	d speed	1500	1800			
.,	m/sec	6.35	7.62			
Mean piston speed	f/sec	20.8	25.0			
Oil consumption		Maximum 0.2% of fuel consumption				

ISO standard conditions and with the provisions specified for continuous power above.

#### De-rating

For non-standard site conditions, reference should be made to relevant BS, ISO and DIN standards.

A comprehensive range of options allows you to select a specification that matches your requirements. Please ask your Lister Petter distributor (see panel below right).

## UK

#### LISTER PETTER LIMITED

Long Street, Dursley, Gloucestershire, GL11 4HS, England TEL: +44 (0)1453 544141; FAX: +44 (0)1453 546732 E-mail: sales@lister-petter.co.uk www.lister-petter.co.uk

## **UAE**

### LISTER PETTER FZE

Dubai Silicon Oasis Headquarters, PO Box 341077, Dubai, UAE TEL: +971 4 372 4331; FAX: +971 4 372 4318 E-mail: sales@listerpettergroup.com www.lister-petter.co.uk

## DISTRIBUTOR'S ADDRESS

Lister Petter have made efforts to ensure that the information in this data sheet is accurate but reserve the right to amend specifications and information without notice and without obligation or liability.